


AirKey cylinder | Scandinavian security cylinder AZ37.SEC



Product description

The AirKey security outdoor cylinder is the optimal solution for doors with Scandinavian lock, where only one-sided authorisation request is needed and additionally in the outdoor area the highest safety level is required.

Technical information

| | |
|--|--|
| Finish | NI - nickel NP - polished nickel MP - polished brass |
| Elongated outside thumbturn axis | AV05 - 5 mm AV10 - 10 mm AV15 - 15 mm |
| Security features | Freely turning outside thumbturn to prevent manipulations Rated brake point on the outside thumbturn Engages only if authorised Event log Plug pulling protection Integrated EAL5+ certified secure element ECDSA and AES encryption |
| Standards and guidelines | CE-certified IP65 protection EN15684 SSF 3522 |
| Technical installation situation | Outside doors with maximum security requirements and subject to tough weather conditions. |
| Compatible identification technologies | NFC smartcards as card identification media, key tags and combi keys Bluetooth 4.0 (BLE) NFC |
| Battery | 2 CR2 lithium batteries Up to 30,000 cycles |
| Signals | Visual + audible |
| Conditions of use | Ambient temperature range: -20°C to +55°C (depending on the battery) Humidity < 90 %, non-condensing For 100,000 cycles Minimum backset 35 mm, IP65 protection |
| Event protocol | Last 1,000 events |
| Interfaces | BLE NFC Connection to emergency power device |
| Included components | AirKey cylinder 2 CR2 lithium batteries Assembly manual Important information |
| Product code | E.A.AI.AZ37.SEC.[Finish].[Option] |
| Example | E.A.AI.AZ37.SEC |



Dimensional drawing

