

FPS Profile cylinder | Portal half cylinder



Product description

The FPS Portal half cylinder in compact design is suitable for portal doors. It locks with an integrated bolt directly into the prepared socket without an rim lock. The cylinder can be locked from one side using the authorised keys. Potential applications are display cabinets and shop windows.

Technical information

System	FPS5 – Functional Profile System 5 pin FPS6 – Functional Profile System 6 pin
Cylinder length on the outside A in mm	31 36 41 +5 ...
Finish	NI – Nickel MS – Brass NP – Polished Nickel NPV – Nickel fully polished MP – Polished brass MPV – Brass fully polished ML – Brass lacquered CR – Chrome CP – Polished chrome CPV – Chrome fully polished PS – Patinated black PB – Patinated brown
Optional technical installation feature	SEW – Sea water protection
Optional usage feature	TXT – Customer-specific text VAR – VARIO
Accessories	Spray FinLube Cylinder fixing screw
Security features	Pin tumbler system cylinder with 5 or 6 active, spring-loaded locking elements Features in the cylinder protect against covert opening methods hardened steel elements for drilling protection
Technical installation situation	For use in portal doors without rim lock
Included components	Cylinder lock without screws
Product code	M.[System].PZ.PHZ.[Outside cylinder length A in mm].[Finish].[Option]
Example	FPS Portal half cylinder 5-pin, length 31 mm, nickel finish, seawater protection optional: M.FPS5.PZ.PHZ.31.NI.SEW

Dimensional drawing

