

# AIRKEY WALL READER SURFACE MOUNT FRAME



## PRODUCT INFORMATION

### SYSTEM PROPERTY

System specification

System type

electronic access systems | offline access systems | combined locking systems

Building type recommended

residential properties | residential complexes | residential buildings for communities | education | health care | industry and trade | office buildings | wholesale and retail | hotels and catering | cultural and leisure time | infrastructure

### FUNCTION

Media technology

JCOP

Function

event memory, last 1.000 events

Signals

acoustic | optical

Encryption

AES | ECDSA | encrypted data transfer

Interfaces

Bluetooth BLE | cable

### USE

Actuation

lockable with access medium | engage only with authorisation

Design feature

elegant design without compromise | timeless

Installation situation

main entrance doors | safety doors | connecting doors | apartment entrance doors | walls

Humidity range

90% at 0°C

Ambient temperature

-25°C to +70°C

## DATASHEET

ELECTRONIC ACCESS SYSTEMS | AIRKEY | WALL READER

### STANDARDS

Directive CE approved | IP65 ingress protection rating

### ASSEMBLY

Assembly special assembly tool required

### INCLUDED COMPONENTS

Included components screw set, disassembly tool, assembly manual, Important information, surface mount frame

### VARIANT

Colour SI – Silver | SW – Black | WS – White

Frame colour SWM – Black | SWP – Polished black | WSM – White | WSP – Polished white | SIM – Silver | SIP – Polished silver

## DIMENSIONAL DRAWING

