

# AIRKEY PADLOCK ANCHOR LAS 848-4WP



## PRODUCT INFORMATION

### SYSTEM PROPERTY

System type	electronic access systems   offline access systems   combined locking systems
Building type recommended	residential properties   residential complexes   residential buildings for communities   education   health care   industry and trade   office buildings   wholesale and retail   hotels and catering   cultural and leisure time   infrastructure

### FUNCTION

Media technology	JCOP
Function	event memory, last 1.000 events
Signals	acoustic   optical
Encryption	AES   encrypted data transfer
Interfaces	Bluetooth BLE   cable

### USE

Actuation	freely rotating outside thumb turn prevents tampering   lockable with access medium   engage only with authorisation
Installation situation	mesh gate   server cabinets   security fences   barrier systems   cellar cubicles   roller shutters
Humidity range	90% at 0°C
Ambient temperature	-20°C to +55°C
Opening cycles, battery set	30.000
Type of power supply	emergency power via programming interface   battery

## DATASHEET

ELECTRONIC ACCESS SYSTEMS | AIRKEY | PADLOCKS

### MATERIAL

Material shackle	hardened steel
------------------	----------------

### STANDARDS

Standard	EN12320_2012 Grade 5   SSF014 V3 Class 4
Directive	CE approved   iP65 ingress protection rating

### ASSEMBLY

Assembly	special assembly tool required
Design features	rated break point on outside thumb turn
Fixing	

### INCLUDED COMPONENTS

Included components	padlock, 2 CR2 lithium batteries, assembly manual, Important information
---------------------	--

### VARIANT

Padlock shackle	BDM15 – Shackle diameter 15 mm   S27 – Steel bracket 27 mm   S50 – Steel shackle. Clearance 50 mm
-----------------	---

## DIMENSIONAL DRAWING

