


AirKey cylinder | Scandinavian security cylinder IZ38.NOR



Product description

The AirKey security indoor cylinder is the optimal solution for doors with Norwegian lock, where only one-sided authorisation request is needed and additionally in the indoor area the highest safety level is required.

Technical information

Finish	NI – nickel NP – polished nickel MP – polished brass
Elongated outside thumbturn axis	AV05 – 5 mm AV10 – 10 mm AV15 – 15 mm
Cylinder escutcheon for AZ38	R0N6 - 6mm R0N8 - 8mm R0N13 - 13mm
Security features	Freely turning outside thumbturn to prevent manipulations Rated brake point on the outside thumbturn Engages only if authorised Event log Plug pulling protection Integrated EAL5+ certified secure element ECDSA and AES encryption
Standards and guidelines	CE-certified IP65 protection EN15684
Technical installation situation	Inside doors with maximum security requirements and subject to tough weather conditions.
Compatible identification technologies	NFC smartcards as card identification media, key tags and combi keys Bluetooth 4.0 (BLE) NFC
Battery	2 CR2 lithium batteries Up to 30,000 cycles
Signals	Visual + audible
Conditions of use	Ambient temperature range: -20° C to +55° C (depending on the battery) Humidity < 90 %, non-condensing For 100,000 cycles Minimum backset 35 mm, IP65 protection
Event protocol	Last 1,000 events
Interfaces	BLE NFC Connection to emergency power device
Included components	AirKey cylinder 2 CR2 lithium batteries Assembly manual Important information
Product code	E.A.AI.IZ38.NOR.[Finish].[Option]
Example	E.A.AI.IZ38.NOR.NI.AV05.R0N6

Dimensional drawing



